

# Copper Clips - LSF Coated RCHJ Red & White



The Range			
List No		Size	Ref No.
RCHL28R	■	2L 1.5, 3L 1.0	28
RCHL30R	■	3L 1.5, 4L 1.0	30
RCHL32R	■	2L 2.5	32
RCHL34R	■	3L 2.5, 4L 1.5	34
RCHL37R	■	4L 2.5	37
RCHL28W	□	2L 1.5, 3L 1.0	28
RCHL30W	□	3L 1.5, 4L 1.0	30
RCHL32W	□	2L 2.5	32
RCHL34W	□	3L 2.5, 4L 1.5	34
RCHL37W	□	4L 2.5	37

Technical Specifications	
<b>Raw Material</b>	Stamped from chamfered edge copper strip C106
<b>Coating:</b>	
<b>Chemical Type</b>	Polyester
<b>Application</b>	Electrostatic Spray
<b>Dry Film Thickness</b>	From 40-100 microns Typically 50 microns
<b>Mechanical Properties:</b>	
<b>Adhesion (BS3900 E3)</b>	Pass 1mm cross-hatch class 0
<b>Impact Resistance (BS3900 E3)</b>	Pass 200'/lb indentation to 2.5mm
<b>Flexibility (BS3900 E11)</b>	Pass 1/4" Conical Mandrel
<b>Ericksen Cupping (BS3900 E4)</b>	Pass 8mm
<b>Scratch Resistance (BS3900 E2)</b>	Pass 400gsm no penetration to substrate
<b>Coating Rating</b>	LSF (Low Smoke and Fume)