


DATASHEET



CFR5CCT

230V IP65 5W Fire-Rated CCT LED Downlight

www.mlaccessories.co.uk



MLA PART CODE	CFR5CCT
DESCRIPTION	230V IP65 5W Fire-Rated CCT LED Downlight
NET WEIGHT (KG)	0.162
FINISH	White
DIMENSIONS (MM)	Diameter - 84 Projection - 4 Overall Height - 58 Recessed Depth - 54 Minimum Void - 105
CUT-OUT (MM)	Cut-out Diameter - 55
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	II
IP RATING	IP65 (IP20 from above)
WATTAGE (W)	5
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	520/560/540
LUMENS LIGHT SOURCE ONLY (LM)	600/620/625
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	126/137/132
CIRCUIT WATTAGE (W)	4.9/4.8/5
CCT	3000/4000/5500K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.028
DISPLACEMENT FACTOR	>0.7
SVM	0.025
PST-LM	0.034
BEAM ANGLE (DEGREES)	55

L70B10 LIFESPAN (HRS)	50,000
DIMMABLE	Yes*
FIRE-RATED	Tested to 30/60/90 minutes
I-JOIST RATED	30 minutes
WEB-JOIST RATED	30 minutes
IC RATED	Yes
ACOUSTIC RATED	Yes
OPERATING TEMPERATURE	25°C
INPUT VOLTAGE	230V 50Hz
DRIVER	EFFICIENCY FULL LOAD - 83.4
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270888010

Date Created: 24/10/2023 09:19

