SIGNATURE

NEMESIS PRO Specification Sheet

Dual Wattage CCT Selectable IP65 Vapour Proof LED Surface Mounted Non-Corrosive Fittings

Our range of Surface Mounted IP65 Vapour Proof LED Non-Corrosive fittings are a great source of light for commercial and industrial spaces, such as garages, car parks, warehouses, workshops, factories, or any other harsh environments that are subject to impact and high humidity.

These CCT dip switch selectable & power selectable are the ideal choice for helping business achieve their energy saving goals, whilst reducing their carbon emissions and giving you individual colour temperature choices to keep housing uniformity throughout the building.



T. J.

Specification

IK Rating	IK08		
CRI	> 80		
IP Rating	IP65		
Working Temp	-15°C - 55°C		
Beam Angle	120°		
Voltage	220 – 240V 50/60Hz		
Power Factor	PF: >0.9		
Material	ABS/Polycarbonate		
ССТ	DIP SWITCH 4000K / 5000K & 6500K		
Warranty	5 years		

Product	Code	Dual Wattages	Lumens Per Watt
4ft Standard	SLL4FTNC/CCT	20w & 40w	120lm/W
4ft Microwave Sensor	SLL4FTNC/CCT/MS	20w & 40w	120lm/W
4ft Emergency	SLL4FTNC/CCT/E	22w & 42w	120lm/W
4ft Emergency Microwave	SLL4FTNC/CCT/E/MS	22w & 42w	120lm/W
5ft Standard	SLL5FTNC/CCT	25w & 50w	120lm/W
5ft Microwave Sensor	SLL5FTNC/CCT/MS	25w & 50w	120lm/W
5ft Emergency	SLL5FTNC/CCT/E	27w & 52w	120lm/W
5ft Emergency Microwave	SLL5FTNC/CCT/E/MS	27w & 52w	120lm/W
6ft Standard	SLL6FTNC/CCT	35w & 70w	120lm/W
6ft Microwave Sensor	SLL6FTNC/CCT/MS	35w & 70w	120lm/W
6ft Emergency	SLL6FTNC/CCT/E	37w & 72w	120lm/W
6ft Emergency Microwave	SLL6FTNC/CCT/E/MS	37w & 72w	120lm/W

LIFE. ILLUMINATED

For more products visit www.signatureledlighting.co.uk