



It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to.

All connections (including factory made) must be checked for the correct tightness prior to commissioning of the electrical installation. All connections should be inspected periodically to ensure correct tightness.

DO NOT USE POWER TOOLS ON THESE PRODUCTS

Europa Helpline: 01582 692 444 / Email: technical@europacomponents.com

Europa House, Airport Way, Luton, Beds, LU2 9NH Tel: 01582 692 440

e-mail: sales@europacomponents.com website: www.europacomponents.com

 ϵ

Part Number: SISRAW63XX IP65/67 63A RCCB Protected Interlocked Socket

Description

- Prewired with 80A Type A RCCB
- Spring-return lid with twist-lock ring ensures IP67 rating.
- Switched Interlocked for added protection.
- 1x M40 cable inlet (Top).
- Stay-on-lid screws included.
- IP65 Enclosure / IP67 Socket





Part Numbers	Amps (A)	Colour & Voltage	Poles	Protection Degree	Terminal Capacity	Recommended Terminal Torque
SISRAW633P	63A	Blue 230 V	2P+E	IP65 Enclosure IP67 Socket	25mm²	2Nm
SISRAW634V		Red 415 V	3P+E			
SISRAW635V		Red 415 V	3P+N+E			

EDS1347-002 Page 1 of 2



Dimensions M40. Note: All dimensions in mm Fixing Dimensions 147 118 160 68 135 26 140 10 198